

PFF19-9002

FRONT WISHBONE REAR BUSH

INSTALLATION GUIDE

Contents (parts per pack):

2 x Polyurethane Bushes

1 x PTFE/Silicone Grease

2 x Stainless Steel Sleeves

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that: -all work to be carried out by a licensed technician;

 -all work to be carried out by a licensed technician -all safety precautions adhered to;

-wheel alignment to be checked and adjusted as required after any suspension work.

-All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Remove the front wishbone from the vehicle.
- 2. Using a workshop press and suitable adapters, push the original bush (including plastic outer shell) out of the arm. This will require snapping the top lip of the outer shell off.
- 3. File away any burrs or sharp edges from the bore and edges of the wishbone, and clean the bore of any dirt/rust.
- 4. Using a small amount of dish soap as lubricant, press the polyurethane bush into the wishbone, with the engraving on the top side of the wishbone (Figure 1).
- 5. Apply the supplied grease to the outside of the stainless steel sleeve and the inside of the bush.
- 6. Push the sleeve into the bush.
- 7. Refit the wishbone to the vehicle, ensuring to tighten all hardware to manufacturer's recommended torque settings.

