

**PART NUMBER** 

# PFF3-1323

**DESCRIPTION** 

### **UPPER ENGINE MOUNT INSERT**

### **INSTALLATION GUIDE**

# Contents (parts per pack):

### 1 x Polyurethane Insert

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual. It is recommended that:

- -all work to be carried out by a licensed technician;
- -all safety precautions adhered to;
- -wheel alignment to be checked and adjusted as required after any suspension work.
- -All fasteners must be tensioned to manufacturer's torque settings.

# SAFETY DURABILITY PERFORMANCE

## **Fitting Instructions:**

- 1. Support the engine from underneath using a trolley jack or axle stand.
- 2. Remove the engine mount from the vehicle and secure it in a vice as shown in Fig 1.
- 3. Fit the polyurethane inserts, one at a time into the voiding of the rubber bush as shown in Fig 2-6.

Tip: To ease fitment, apply a small amount of washing-up liquid to the inserts prior to assembly and wiggle the mount from side to side whilst applying pressure to the insert.

- 4. Refit the mount to the vehicle and tension all hardware to the manufacturer's recommended torque settings.
- 5. Remove the support from underneath the engine.



Figure 1



Figure 2



Figure 3



Figure 4



Figure 5



Figure 6